

SOILS

— THE TOUGHEST —
PERFORMER
« FOR YOUR FIELD »

26



RELIABLE MECHANICAL
TRACTOR

POWER PACKED
ENGINE

TWIN PROJECTOR
HEADLAMPS

AGRI, IND & TURF
TYRE OPTION

REINFORCED SAFETY
FEATURES



**COST
EFFICIENT**
MECHANICAL TRACTORS

MADE OF
**REAL
STEEL**

**STRATEGIC
COLLABORATION
WITH
YANMAR**

THE TOUGHEST PERFORMER FOR YOUR FIELD

S 26

Solis



FEATURES	S 26
Model Description	SOLIS-26
ENGINE	
Engine Type	Mitsubishi 3 Cylinder
HP Category	26
No. of Cylinders	3
Aspiration	Natural
Cubic Capacity (cc)	1318
Rated RPM (+/-25mm)	2700
Air cleaner	Dry
Cold Start	Yes
Max Torque (Nm)	76.3
Exhaust	Underhood Downdraft Silencer
TRANSMISSION	
Drive	4WD
Clutch	Single Clutch
Gearbox	6F+2R
Front Axle	4WD
Transmission	Sliding Mesh
SPEED (FORWARD)	
Maximum Speed (Km/Hr)	15.58 @ 2700
Minimum Speed (Km/Hr)	1.67 @ 2700
BRAKES	
Brakes	Oil Immersed Brakes
Type of actuation	Mechanical
Parking Brake	Independent
DIFFERENTIAL LOCK	
Differential lock	Yes, Foot Operated
PTO	
PTO (rpm)	540, 1000
PTO (actuation)	Mechanical
STEERING	
Steering	Power
ELECTRICAL	
Battery	12V, 65Ah
Type of Actuation	12V, 42Amp
Parking Brake	Yes
HYDRAULICS	
3 point linkage	Cat-I
Stay Bars	Anchor Chain
Auxiliary hydraulic circuit	1DA
Lift rods	Yes
Litre per minute(LPM)	12

FEATURES	S 26
SAFETY SWITCH	
Clutch Safety Switch	Yes
PTO Safety Switch	Yes
Neutral Safety Switch	Yes
CAPACITY (LTRS)(+/-5%)	
Fuel tank (Lit)	26.5
TURNING RADIUS	
Without Brakes (m)	2.7
TYRE	
Front	6.00-12
Rear	8.30-20
DIMENSION & WEIGHT(+/-5%)	
Weight(kg)	960
Wheel Base (mm)	1560
Total Length (mm)	2725
Total Width (mm)	1058
Height (mm) Up to ROPS	2127
Min Ground Clearance (mm)	255
Front Track (mm)	894
Rear Track (mm)	825
OTHERS	
Fuel Indicator gauge	Yes
Front Toe Hook	Yes
Front & rear weights with std. Ballast	Front weights-15x2
Trailer Hitch	1. Clevis Hitch 2. Swinging Drawbar (Optional)
ROPS	Yes
OPTIONAL FEATURES	
Tyres	TURF TYRES: Front Tyre - 23x8.50-12 Rear tyre - 33x15.50-16.5 INDUSTRIAL TYRES: Front tyre- 23x8.50-12 Rear tyre- 33x15.50-16.5